

07/13/00
JC658 U.S. PTO

Please type a plus sign (+) inside this box → ☐

PTO/SB/05 (4/98)
Approved for use through 09/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No.	KDO:190230-4
First Inventor or Application Identifier	Jordi Ribas-Corbera
Title	METHODS FOR MOTION ESTIMATION WITH...
Express Mail Label No.	

APPLICATION ELEMENTS
See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

- ☒ * Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
- ☒ Specification [Total Pages 23]
(preferred arrangement set forth below)
 - Descriptive title of the invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the invention
 - Brief Summary of the invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
- ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 16]
- Oath or Declaration [Total Pages 3]
 - ☒ Newly executed (original or copy)
 - ☐ Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 16 completed)
 - ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b)

- ☐ Microfiche Computer Program (Appendix)
- Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - ☐ Computer Readable Copy
 - ☐ Paper Copy (identical to computer copy)
 - ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

- ☐ Assignment Papers (cover sheet & document(s))
- ☐ 37 C.F.R. § 3.73(b) Statement (when there is an assignee) ☐ Power of Attorney
- ☐ English Translation Document (if applicable)
- ☒ Information Disclosure Statement (IDS)/PTO-1449 ☒ Copies of IDS Citations
- ☐ Preliminary Amendment
- ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
- ☐ * Small Entity Statement(s) ☐ Statement filed in prior application, Status still proper and desired (PTO/SB/09-12)
- ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
- ☒ Other: Petition for License for Foreign Filing

* NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:
☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. _____
Prior application information: Examiner _____ Group / Art Unit: _____

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label (Insert Customer No. or Attach bar code label here) or ☒ Correspondence address below

Name	Karen Dana Oster Miller Nash LLP				
Address	3500 U.S. Bancorp Tower 111 S.W. Fifth Avenue				
City	Portland	State	Oregon	Zip Code	97204
Country	USA	Telephone	(503) 224-5858	Fax	(503) 224-0155

Name (Print/Type)	Karen Dana Oster	Registration No. (Attorney/Agent)	37,621
Signature	<i>Karen Oster</i>	Date	July 12, 2000

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

METHODS FOR MOTION ESTIMATION WITH ADAPTIVE MOTION ACCURACY

BACKGROUND OF THE INVENTION

5 The present invention relates generally to a method of compressing or coding digital video with bits and, specifically, to an effective method for estimating and encoding motion vectors in motion-compensated video coding.

 In classical motion estimation the current frame to be encoded is decomposed into image blocks of the same size, typically blocks of 16x16 pixels, called
10 "macroblocks." For each current macroblock, the encoder searches for the block in a previously encoded frame (the "reference frame") that best matches the current macroblock. The coordinate shift between a current macroblock and its best match in the reference frame is represented by a two-dimensional vector (the "motion vector") of the macroblock. Each component of the motion vector is measured in pixel units.

15 For example, if the best match for a current macroblock happens to be at the same location, as is the typical case in stationary background, the motion vector for the current macroblock is (0,0). If the best match is found two pixels to the right and three pixels up from the coordinates of the current macroblock, the motion vector is (2,3). Such motion vectors are said to have integer pixel (or "integer-pel" or "full-pel")
20 accuracy, since their horizontal X and vertical Y components are integer pixel values. In FIG. 1, the vector $V_1 = (1,1)$ represents the full-pel motion vector for a given current macroblock.

 Moving objects in a video scene do not move in integer pixel increments from frame to frame. True motion can take any real value along the X and Y directions.
25 Consequently, a better match for a current macroblock can often be found by interpolating the previous frame by a factor $N \times N$ and then searching for the best match in the interpolated frame. The motion vectors can then take values in increments of $1/N$ pixel along X and Y and are said to have $1/N$ pixel (or "1/N-pel") accuracy.

In "Response to Call for Proposals for H.26L," ITU-Telecommunications Standardization Sector, Q.15/SG16, doc. Q15-F-11, Seoul, Nov. 98, and "Enhancement of the Telenor proposal for H.26L," ITU-Telecommunications Standardization Sector, Q.15/SG16, doc. Q15-G-25, Monterey, Feb. 99, Gisle Bjontegaard proposed using 1/3-pel accurate motion vectors and cubic-like interpolation for the H26L video coding standard (the "Telenor encoder"). To do this, the Telenor encoder interpolates or "up-samples" the reference frame by 3x3 using a cubic-like interpolation filter. This interpolated version requires nine times more memory than the reference frame. At a given macroblock, the Telenor encoder estimates the best motion vector in two steps: the encoder first searches for the best integer-pel vector and then the Telenor encoder searches for the best 1/3-pixel accurate vector $V_{1/3}$ near V_1 . Using FIG. 1 as an example, a total of eight blocks (of 16x16 pixels) in the 3x3 interpolated reference frame are checked to find the best match which, as shown is the block associated to the motion vector $V_{1/3} = (VX, VY) = (1+1/3, 1)$. The Telenor encoder has several problems. First, it uses a sub-optimal fast-search strategy and a complex cubic filter (at all stages) to compute the 1/3-pel accurate motion vectors. As a result, the computed motion vectors are not optimal and the memory and computation requirements are very expensive. Further, the Telenor encoder uses an accuracy of the effective rate-distortion criteria that is fixed at 1/3-pixel and, therefore, does not adapt to select better motion accuracies. Similarly, the Telenor encoder variable-length code ("VLC") table has an accuracy fixed at 1/3-pixel and, therefore, is not adapted and interpreted differently for different accuracies.

Most known video compression methods estimate and encode motion vectors with 1/2-pixel accuracy, because early studies suggested that higher or adaptive motion accuracies would increase computational complexity without providing additional compression gains. These early studies, however, did not estimate the motion vectors using optimized rate-distortion criteria, did not exploit the convexity properties of such criteria to reduce computational complexity, and did not use effective strategies to encode the motion vectors and their accuracies.

One such early study was Bernd Girod's "Motion-Compensating Prediction with Fractional-Pel Accuracy," IEEE Transactions on Communications, Vol. 41, No. 4, pp. 604-612, April 1993 (the "Girod work"). The Girod work is the first fundamental analysis on the benefits of using sub-pixel motion accuracy for video coding. Girod used a simple, hierarchical strategy to search for the best motion vector in sub-pixel space. He also used simple mean absolute difference ("MAD") criteria to select the best motion vector for a given accuracy. The best accuracy was selected using a formula that is not useful in practice since it is based on idealized assumptions, is very complex, and restricts all motion vectors to have the same accuracy within a frame. Finally, Girod focused only on prediction error energy and did not address how to use bits to encode the motion vectors.

Another early study was Smita Gupta's and Allen Gersho's "On Fractional Pixel Motion Estimation," Proc. SPIE VCIP, Vol. 2094, pp. 408-419, Cambridge, November 1993 (the "Gupta work"). The Gupta work presented a method for computing, selecting, and encoding motion vectors with sub-pixel accuracy for video compression. The Gupta work disclosed a formula based on mean squared error ("MSE") and bilinear interpolation, used this formula to find an ideal motion vector, and then quantized such vector to the desired motion accuracy. The best motion vector for a given accuracy was found using the sub-optimal MSE criteria and the best accuracy was selected using the largest decrease in difference energy per distortion bit, which is a greedy (sub-optimal) criteria. A given motion vector was coded by first encoding that vector with 1/2-pel accuracy and then encoding the higher accuracy with refinement bits. Course-to-fine coding tends to require significant bit overhead.

In "On the Optimal Motion Vector Accuracy for Block-Based Motion-Compensated Video Coders," Proc. IST/SPIE Digital Video Compression: Algorithms and Technologies, pp. 302-314, San Jose, February 1996 (the "Ribas work"), Jordi Ribas-Corbera and David L. Neuhoff, modeled the effect of motion accuracy on bit rate and proposed several methods to estimate the optimal accuracies that minimize bit rate. The Ribas work set forth a full-search approach for computing motion vectors for a given

accuracy and considered only bilinear interpolation. The best motion vector was found by minimizing MSE and the best accuracy was selected using some formulas derived from a rate-distortion optimization. The motion vectors and accuracies were encoded with frame-adaptive entropy coders, which are complex to implement in real-time applications.

In "Proposal for a new core experiment on prediction enhancement at higher bitrates," ISO/IEC JTC1/SC29/WG11 Coding of Moving Pictures and Audio, MPEG 97/1827, Sevilla, Feb. 1997 and "Performance Evaluation of a Reduced Complexity Implementation for Quarter Pel Motion Compensation," ISO/IEC JTC1/SC29/WG11 Coding of Moving Pictures and Audio, MPEG 97/3146, San Jose, Jan. 1998, Ulrich Benzler proposed using 1/4-pel accurate motion vectors for the video sequence and more advanced interpolation filters for the MPEG4 video coding standard. Benzler, however, used the Girod's fast-search technique to find the 1/4-pel motion vectors. Benzler did consider different interpolation filters, but proposed a complex filter at the first stage and a simpler filter at the second stage and interpolated one macroblock at a time. This approach does not require much cache memory, but it is computationally expensive because of its complexity and because all motion vectors are computed with 1/4-pel accuracy for all the possible modes in a macroblock (e.g., 16x16, four-8x8, sixteen-4x4, etc.) and then the best mode is determined. Benzler used the MAD criteria to find the best motion vector which was fixed to 1/4-pel accuracy for the whole sequence, and hence he did not address how to select the best motion accuracy. Finally, Benzler encoded the motion vectors with a variable-length code ("VLC") table that could be used for encoding 1/2 and 1/4 pixel accurate vectors.

The references discussed above do not estimate the motion vectors using optimized rate-distortion criteria and do not exploit the convexity properties of such criteria to reduce computational complexity. Further, these references do not use effective strategies to encode motion vectors and their accuracies.

BRIEF SUMMARY OF THE INVENTION

One preferred embodiment of the present invention addresses the problems of the prior art by computing motion vectors of high pixel accuracy (also denoted as "fractional" or "sub-pixel" accuracy) with a minor increase in computation.

5 Experiments have demonstrated that, by using the search strategy of the present invention, a video encoder can achieve significant compression gains (e.g., up to thirty percent in bit rate savings over the classical choices of motion accuracy) using similar levels of computation. Since the motion accuracies are adaptively computed and selected, the present invention may be described as adaptive motion accuracy ("AMA").

10 One preferred embodiment of the present invention uses fast-search strategies in sub-pixel space that smartly searches for the best motion vectors. This technique estimates motion vectors in motion-compensated video coding by finding a best motion vector for a macroblock. The first step is searching a first set of motion vector candidates in a grid of sub-pixel resolution of a predetermined square radius centered on V_1 to find a best motion vector V_2 . Next, a second set of motion vector candidates in a grid of sub-pixel resolution of a predetermined square radius centered on V_2 is searched to find a best motion vector V_3 . Then, a third set of motion vector candidates in a grid of sub-pixel resolution of a predetermined square radius centered on V_3 is searched to find the best motion vector of the macroblock.

20 In an alternate preferred embodiment the present invention a technique for estimating high-accurate motion vectors may use different interpolation filters at different stages in order to reduce computational complexity.

Another alternate preferred embodiment of the present invention selects the best vectors and accuracies in a rate-distortion ("RD") sense. This embodiment uses rate-distortion criteria that adapts according to the different motion accuracies to determine both the best motion vectors and the best motion accuracies.

Still further, another alternate preferred embodiment of the present invention encodes the motion vector and accuracies with an effective VLC approach.

This technique uses a VLC table that is interpreted differently at different coding units, according to the associated motion vector accuracy.

The foregoing and other objectives, features, and advantages of the invention will be more readily understood upon consideration of the following detailed description of the invention, taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

FIG. 1 is a diagram of an exemplary full-pel and 1/3-pel locations in velocity space.

FIG. 2 is a flowchart illustrating a prior art method for estimating the best motion vector.

FIG. 3 is a diagram of an exemplary location of motion vector candidates for full-search in sub-pixel velocity space.

FIG. 4 is a flowchart illustrating a full-search preferred embodiment of the method for estimating the best motion vector of the present invention.

FIG. 5 is a diagram of an exemplary location of motion vector candidates for fast-search in sub-pixel velocity space.

FIG. 6 is a flowchart illustrating a fast-search preferred embodiment of the method for estimating the best motion vector of the present invention.

FIG. 7 is a detail flowchart illustrating an alternate preferred embodiment of step 114 of FIG. 6.

FIG. 8 is a graphical representation of experimental performance results of the Telenor encoder with and without AMA in the "Container" video sequence, with QCIF resolution, and at the frame rate of 10 frames per second.

FIG. 9 is a graphical representation of experimental performance results of the Telenor encoder with and without AMA in the "News" video sequence, with QCIF resolution, and at the frame rate of 10 frames per second.

FIG. 10 is a graphical representation of experimental performance results of the Telenor encoder with and without AMA in the "Mobile" video sequence, with QCIF resolution, and at the frame rate of 10 frames per second.

5 FIG. 11 is a graphical representation of experimental performance results of the Telenor encoder with and without AMA in the "Garden" video sequence, with SIF resolution, and at the frame rate of 15 frames per second.

FIG. 12 is a graphical representation of experimental performance results of the Telenor encoder with and without AMA in the "Garden" video sequence, with QCIF resolution, and at the frame rate of 15 frames per second.

10 FIG. 13 is a graphical representation of experimental performance results of the Telenor encoder with and without AMA in the "Tempete" video sequence, with SIF resolution, and at the frame rate of 15 frames per second.

FIG. 14 is a graphical representation of experimental performance results of the Telenor encoder with and without AMA in the "Tempete" video sequence, with QCIF resolution, and at the frame rate of 15 frames per second.

FIG. 15 is a graphical representation of experimental performance results of the Telenor encoder with and without AMA in the "Paris shaken" video sequence, with QCIF resolution, and at the frame rate of 10 frames per second.

20 FIG. 16 is a graphical representation of experimental performance results of fast-search ("Telenor FSAMA+c") and full-search ("Telenor AMA+c") strategies in the "Mobile" video sequence, with QCIF resolution, and at the frame rate of 10 frames per second.

FIG. 17 is a graphical representation of experimental performance results of fast-search ("Telenor FSAMA+c") and full-search ("Telenor AMA+c") strategies in the "Container" video sequence, with QCIF resolution, and at the frame rate of 10 frames per second.

FIG. 18 is a graphical representation of experimental performance results of tests using only one reference frame for motion compensation as compared to tests

using multiple reference frames for motion compensation the in the "Mobile" video sequence, with QCIF resolution, and at the frame rate of 10 frames per second.

DETAILED DESCRIPTION OF THE INVENTION

5 The methods of the present invention are described herein in terms of the motion accuracy being modified at each image block. These methods, however, may be applied when the accuracy is fixed for the whole sequence or modified on a frame-by-frame basis. The present invention is also described as using Telenor's video encoders (and particularly the Telenor encoder) as described in the Background of the Invention. Although
10 described in terms of Telenor's video encoders, the techniques described herein are applicable to any other motion-compensated video coder.

Most video coders use motion vectors with half pixel (or "1/2-pel") accuracy and bilinear interpolation. The first version of Telenor's encoder also used 1/2-pel motion vectors and bilinear interpolation. The latest version of Telenor's encoder, however,
15 incorporated 1/3-pel vectors and cubic-like interpolation because of the additional compression gains. Specifically, at a given macroblock, Telenor's estimates the best motion vector in two steps shown in FIG. 2. First, the Telenor encoder searches for the best integer-pel vector V_1 (FIG. 1) 100. Second, the Telenor encoder searches for the best 1/3-pixel accurate vector $V_{1/3}$ (FIG. 1) near V_1 102. This second step is shown graphically in FIG. 1
20 where a total of eight blocks (each having an array of 16x16 pixels) in the 3x3 interpolated reference frame are checked to find the best match. The motion vectors for these eight blocks are represented by the eight solid dots in the grid centered on V_1 . In FIG. 1 the best match is the block associated to the motion vector $V_{1/3} = (V_x, V_y) = (1+1/3, 1)$.

The technology of the present invention allows the encoder to choose
25 between any set of motion accuracies (for example, 1/2, 1/3, and 1/6-pel accurate motion vectors) using either a full search strategy or a fast search strategy.

Full-Search AMA Search Strategy

As shown in FIGS. 3 and 4, in the full-search adaptive motion accuracy ("AMA") search strategy the encoder searches all the motion vector candidates in a grid of 1/6-pixel resolution and a "square radius" (defined herein as a square block defined by a number of pixels up, a number of pixels down, and a number of pixels to both sides) of five pixels as shown in FIG. 3. FIG. 4 shows that the first step of the full-search AMA is to search for the best integer-pel vector V_1 (FIG. 1) 104. In the second step of the full-search AMA, the encoder searches for the best 1/6-pixel accurate vector $V_{1/6}$ (FIG. 3) near V_1 106. In other words, the full-search AMA modifies the second step of the Telenor's process so that the encoder also searches for motion vector candidates in other sub-pixel locations in the velocity space. The objective is to find the best motion vector in the grid, i.e., the vector that points to the block (in the interpolated reference frame) that best matches the current macroblock. Although the full-search strategy is computationally complex since it searches 120 sub-pixel candidates, it shows the full potential of this preferred method of the present invention.

A critical issue in the motion vector search is the choice of a measure or criterion for establishing which block is the best match for the given macroblock. In practice, most methods use either the mean squared error ("MSE") or mean absolute difference ("MAD") criteria. The MSE between two blocks consists of subtracting the pixel values of the two blocks, squaring the pixel differences, and then taking the average. The MAD difference between two blocks is a similar distortion measure, except that the absolute value of the pixel differences is computed instead of the squares. If two image blocks are similar to each other, the MSE and MAD values will be small. If, however, the image blocks are dissimilar, these values will be large. Hence, typical video coders find the best match for a macroblock by selecting the motion vector that produces either the smallest MSE or the smallest MAD. In other words, the block associated to the best motion vector is the one closest to the given macroblock in an MSE or MAD sense.

Unfortunately, the MSE and MAD distortion measures do not take into account the cost in bits of actually encoding the vector. For example, a given motion

vector may minimize the MSE, but it may be very costly to encode with bits, so it may not be the best choice from an coding standpoint.

To deal with this, advanced encoders such as those described by Telenor use rate-distortion ("RD") criteria of the type "distortion + L*Bits" to select the best motion vector. The value of "distortion" is typically the MSE or MAD, "L" is a constant that depends on the compression level (i.e., the quantization step size), and "Bits" is the number of bits required to code the motion vector. In general, any RD criteria of this type would work with the present invention. However, in the present invention "Bits" include the bits needed for encoding the vector and those for encoding the accuracy of the vector. In fact, some candidates can have several "Bits" values, because they can have several accuracy modes. For example, the candidate at location (1/2, -1/2) can be thought of having 1/2 or 1/6 pixel accuracy.

Fast-Search AMA Search Strategy

As shown in FIGS. 5 and 6, in the fast-search adaptive motion accuracy ("AMA") search strategy the encoder checks only a small set of the motion vector candidates. In the first step of the fast-search AMA, the encoder checks the eight motion vector candidates in a grid of 1/2-pixel resolution of square radius 1, which is centered on V_1 108. V_2 is then set to denote the candidate that has the smallest RD cost (i.e., the best of the eight previous vectors and V_1) 110. Next, the encoder checks the eight motion vector locations in a grid of 1/6-pixel resolution of square radius 1 that is now centered on V_2 112. If V_2 has the smallest RD cost 114, the encoder stops its search and selects V_2 as the motion vector for the block. Otherwise, V_3 is set to denote the best motion vector of the eight 116. The encoder then searches for a new motion vector candidates in the grid of 1/6-pixel resolution of square radius 1 that is centered on V_3 118. It should be noted that some of the candidates in this grid have already been tested and can be skipped. The candidate with the smallest RD cost in this last step is selected as the motion vector for the block 120.

Experimental data has shown that, on average, this simple fast search strategy typically checks the RD cost of about eighteen locations in sub-pixel space (ten more than

Telenor's search strategy), and hence the overall computational complexity is only moderately increased.

The experimental data discussed below in connection with FIGS. 8-18 show that there is practically no loss in compression performance from using this fast-search version of AMA. This is because the fast-search AMA search strategy exploits the convexity of the "distortion + L*Bits" curve (c.f., "distortion" is known to be convex), by creating a path that smartly follows the RD cost from higher to lower levels.

Alternate embodiments of the invention replace one or more of the steps 108-120. These embodiments have also been effective and have further reduced the number of motion vector candidates to check in the sub-pixel velocity space.

FIG. 7, for example, checks candidates of 1/3-pel accuracy. In this embodiment step 112 is replaced by one of three possible scenarios. First, if the best motion vector candidate from step 110 is at the center of V_1 (the "integer-pel vector") 130, then the encoder checks three candidates of 1/3-pel accuracy between the center vector and the 1/2-pel location with the next lowest RD cost 132. Second, if the best motion vector candidate from step 110 is a corner vector 134, then, the encoder checks the four vector candidates of 1/3-pel accuracy that are closest to such corner 136. Third, if the best motion vector candidate from step 110 is between two corners 138, then, the encoder determines which of these two corners has lower RD cost and checks the four vector candidates of 1/3-pel accuracy that are closest to the line between such corner and the best candidate from step 110 140. It should be noted that in implementing this process step 138 may be unnecessary because if V_2 is neither at the center or a corner vector, then it would necessarily be between two corners. If the encoder is set to find motion vectors with 1/3-pixel accuracy, FIG. 7 could be modified to end rather than continuing with step 114.

Computation And Memory Savings

Because step 108 checks only motion vector candidates of 1/2-pixel accuracy, the computation and memory requirements for the hardware or software implementation are significantly reduced. To be specific, in a smart implementation

embodiment of this fast-search the reference frame is interpolated by 2x2 in order to obtain the RD costs for the 1/2-pel vector candidates. A significant amount of fast (or cache) memory for a hardware or software encoder is saved as compared to Telenor's approach that needed to interpolate the reference frame by 3x3. In comparison to the Telenor encoder, this is a cache memory savings of 9/4 or a factor of 2.25. The few additional interpolations can be done later on a block-by-block basis.

Additionally, since the interpolations in step 108 are used to direct the search towards the lower values of the RD cost function, a complex filter is not needed for these interpolations. Accordingly, computation power may be saved by using a simple bilinear filter for step 108.

Also, other key coding decisions such as selecting the mode of a macroblock (e.g., 16x16, four-8x8, etc.) can be done using the 1/2-pel vectors because such decisions do not benefit significantly from using higher accuracies. Then, the encoder can use a more complex cubic filter to interpolate the required sub-pixel values for the few additional vector candidates to check in the remaining steps. Since the macroblock mode has already been chosen, these final interpolations only need to be done for the chosen mode.

Use of multiple-filters obtained computation savings of over twenty percent in running time on a Sparc Ultra 10 Workstation in comparison to Telenor's approach, which uses a cubic interpolation all the time. Additionally, the fast-memory requirements were reduced by nearly half. Also, there was little or no loss in compression performance. Comparing one preferred embodiment of the fast-search, Benzler's technique requires about 70 interpolations per pixel in the Telenor encoder and the present invention requires only about 7 interpolations per pixel.

Coding The Motion Vector And Accuracies With Bits

Once the best motion vector and accuracy are determined, the encoder encodes both the motion vector and accuracy values with bits. One approach is to encode the motion vector with a given accuracy (e.g., half-pixel accuracy) and then add some extra

bits for refining the vector to the higher motion accuracy. This is the strategy suggested by B. Girod, but it is sub-optimal in a rate-distortion sense.

In one preferred embodiment of the present invention, the accuracy of the motion vector for a macroblock is first encoded using a simple code such as the one given in Table 1. Any other table with code lengths {1, 2, 2} could be used as well. The bit rate could be further reduced using a typical DPCM approach.

Code	Motion Accuracy
1	1/2-pel
01	1/3-pel
11	1/6-pel

Table 1. VLC table to indicate the accuracy mode for a given macroblock.

Next, the value of the vector/s in the respective accuracy space is encoded. These bits can be obtained from entries of a single VLC table such as the one used in the H26L codec. The key idea is that these bits are interpreted differently depending on the motion accuracy for the macroblock. For example, if the motion accuracy is 1/3 and the code bits for the X component of the difference motion vector are 000011, the X component of the vector is $V_x = 2/3$. If the accuracy is 1/2, such code corresponds to $V_x = 1$.

Compared to the Benzler method for encoding the motion vectors with a variable length code ("VLC") table that could be used for encoding 1/2 and 1/4 pixel accurate vectors, the method of the present invention can be used for encoding vectors of any motion accuracy and the table can be interpreted differently at each frame and macroblock. Further, the general method of the present invention can be used for any motion accuracy, not necessarily those that are multiples of each other or those that are of the type 1/n (with n an integer). The number of increments in the given sub-pixel space is simply counted and the bits in the associated entry of the table is used as the code.

1 Observe that this code is the fourth entry (code number 3) of H26L's VLC table in [6].

From the decoder's viewpoint, once the motion accuracy is decoded, the motion vector can also be easily decoded. After that, the associated block in the previous frame is reconstructed using a typical 4-tap cubic interpolator. There is a different 4-tap filter for each motion accuracy.

5 The AMA does not increase decoding complexity, because the number of operations needed to reconstruct the predicted block are the same, regardless of the motion accuracy.

Experimental Results

10 FIGS. 8-18 show test results of the Telenor encoder codec with and without AMA in a variety of video sequences, resolutions, and frame rates, as described in Table 2. These figures show rate-distortion ("RD") plots for each case. The "Anchor" curve shows RD points from optimized H.263+ (FIGS. 8 and 9 only). The "Telenor 1/2+b" curve shows Telenor with 1/2-pel vectors and bilinear interpolation (the "classical case"). The "Telenor 1/3" curve shows the current Telenor proposal (the "Telenor encoder"). The "Telenor+AMA+c" curve shows the Telenor encoder with the full-search strategy of the present invention. The "Telenor +FSAMA+c", as shown in FIGS. 15-17, shows the current Telenor encoder with the fast-search strategy. (Unless otherwise specified, the full-search version of AMA was the encoder strategy used in the experiments.) All of the test results were cross-checked at the encoder and decoder. These results show that with AMA the gains in peak signal-to-noise ratio ("PSNR") can be as high as 1 dB over H26L, and even higher over the classical case.

Video sequence	FIG. #	Resolution	Frame rate
Container	FIG. 8	QCIF	10
News	FIG. 9	QCIF	10
Mobile	FIG. 10	QCIF	10

	FIG. 11	SIF	15
Garden	FIG. 12	QCIF	15
Tempete	FIG. 13	SIF	15
	FIG. 14	QCIF	15
Paris Shaked	FIG. 15	QCIF	10

Table 2. Description of the Experiments

The video sequences are commonly used by the video coding community, except for “Paris Shaked.” The latter is a synthetic sequence obtained by shifting the well-known sequence “Paris” by a motion vector whose X and Y components take a random value within $[-1,1]$. This synthetic sequence simulates small movements caused by a hand-held camera in a typical video phone scene.

Comparison Of Full-Search And Fast-Search AMA

The experimental results shown in FIGS. 16 and 17 demonstrate that the encoder performance with fast-search (“Telenor FSAMA+c”) and full-search (“Telenor AMA+c”) strategies for AMA is practically the same. This is true because the fast-search strategies exploit the convexity of the RD cost curve in the sub-pixel velocity space. In other words, since the shape of the RD cost follows a smooth convex curve, its minimum should be easy to find with some smart fast-search schemes that descend down the curve.

Combining AMA And Multiple Reference Frames

In the plot shown in FIG. 18, the curves labeled “1r” used only one reference frame for the motion compensation, so these curves are the same as those presented in FIG. 10. The curves labeled “5r” used five reference frames.

The experiments show that the gains with AMA add to those obtained using multiple reference frames. The gain from AMA in the one-reference case can be measured by comparing the green and pink curves, and the gain in the five-reference case can be measured between the blue and red curves.

It should be noted that the present invention may be implemented at the frame level so that different frames could use different motion accuracies, but within a frame all motion vectors would use the same accuracy. Preferably in this embodiment the motion vector accuracy would then be signaled only once at the frame layer. Experiments have shown that using the best, fixed motion accuracy for the whole frame should also produce compression gains as those presented here for the macroblock-adaptive case.

In another frame-based embodiment the encoder could do motion compensation on the entire frame with the different vector accuracies and then select the best accuracy according to the RD criteria. This approach is not suitable for pipeline, one-pass encoders, but it could be appropriate for software-based or more complex encoders. Still another frame-based embodiment the encoder could use previous statistics and/or formulas to predict what will be the best accuracy for a given frame (e.g., the formulas in set forth in the Ribas work or a variation thereof can be used). This approach would be well-suited for one-pass encoders, although the performance gains would depend on the precision of the formulas used for the prediction.

The terms and expressions which have been employed in the foregoing specification are used therein as terms of description and not of limitation, and there is no intention, in the use of such terms and expressions, of excluding equivalents of the features shown and described or portions thereof, it being recognized that the scope of the invention is defined and limited only by the claims that follow.

WHAT IS CLAIMED IS:

1. A fast-search adaptive motion accuracy search method for estimating motion vectors in motion-compensated video coding by finding a best motion vector for a macroblock, said method comprising the steps of:

- 5 (a) searching a first set of motion vector candidates in a grid of sub-pixel resolution of a predetermined square radius centered on V_1 to find a best motion vector V_2 ;
- (b) searching a second set of motion vector candidates in a grid of sub-pixel resolution of a predetermined square radius centered on V_2 to find a best motion vector V_3 ; and
- 10 (c) searching a third set of motion vector candidates in a grid of sub-pixel resolution of a predetermined square radius centered on V_3 to find said best motion vector of said macroblock.

- 15 2. The method of claim 1, said step of searching a first set of motion vector candidates in a grid of sub-pixel resolution of a predetermined square radius centered on V_1 to find a best motion vector V_2 further comprising the step of searching a first set of eight motion vector candidates in a grid of 1/2-pixel resolution of square radius 1 centered on V_1 to find a best motion vector V_2 .

- 20 3. The method of claim 1, said step of searching a second set of motion vector candidates in a grid of sub-pixel resolution of a predetermined square radius centered on V_2 to find a best motion vector V_3 further comprising the step of searching a second set of eight motion vector candidates in a grid of 1/6-pixel resolution of square radius 1 centered
- 25 on V_2 to find a best motion vector V_3 .

4. The method of claim 1 further comprising the steps of using V_2 as the motion vector for the block if V_2 has the smallest rate-distortion cost and skipping step (c) of claim 1.

5. The method of claim 1, said step of searching a third set of motion vector candidates in a grid of sub-pixel resolution of a predetermined square radius centered on V_3 to find said best motion vector of said macroblock further comprising the step of
5 searching a third set of eight motion vector candidates in a grid of 1/6-pixel resolution of square radius 1 centered on V_3 to find said best motion vector of said macroblock.

6. The method of claim 1, said step of searching a third set of motion vector candidates in a grid of sub-pixel resolution of a predetermined square radius centered
10 on V_3 to find said best motion vector of said macroblock further comprising the step of skipping motion vector candidates of said third set of motion vector candidates that have already been tested.

7. The method of claim 1 further wherein said step of searching said first
15 set of motion vector candidates further comprises the step of searching said first set of motion vector candidates using a first filter to do a first interpolation, said step of searching said second set of motion vector candidates further comprises the step of searching said second set of motion vector candidates using a second filter to do a second interpolation, and
20 said step of searching said third set of motion vector candidates further comprises the step of searching said third set of motion vector candidates using a third filter to do a third interpolation.

8. The method of claim 1, said step of searching a second set of motion vector candidates in a grid of sub-pixel resolution of a predetermined square radius centered
25 on V_2 to find a best motion vector V_3 further comprising the steps of:

- (a) searching three candidates of 1/3-pel accuracy V_2 and a 1/2-pel location with the next lowest RD cost if V_2 is at the center;
- (b) searching four vector candidates of 1/3-pel accuracy that are closest to V_2 if V_2 is a corner vector; and

- (c) determining which of two corners has lower RD cost and searching four vector candidates of 1/3-pel accuracy that are closest to a line between said corner with lower RD cost, if V_2 is between two corners vectors.

5

9. An adaptive motion accuracy search method for estimating motion vectors in motion-compensated video coding by finding a best motion vector for a macroblock, said method comprising the steps of:

- (a) searching a first set of motion vector candidates in a grid centered on V_1 to find a best motion vector V_2 using a first filter to do a first interpolation;
- (b) searching a second set of motion vector candidates in a grid centered on V_2 to find a best motion vector V_3 using a second filter to do a second interpolation; and
- (c) searching a third set of motion vector candidates in a grid centered on V_3 to find said best motion vector of said macroblock using a third filter to do a third interpolation.

10

10. The method of claim 9 wherein said step of searching using a first filter to do a first interpolation further comprises using a simple filter to do a coarse interpolation.

15

11. The method of claim 9 wherein said step of searching using a first filter to do a first interpolation further comprises using a simple filter to do a coarse interpolation and said step of searching using a second filter to do a second interpolation further comprises using a complex filter to do a fine interpolation.

20

25

12. The method of claim 11 wherein said step of searching using a third filter to do a third interpolation further comprises using a complex filter to do a fine interpolation.

5 13. The method of claim 9 wherein said step of searching using a first filter to do a first interpolation further comprises using a bilinear filter to interpolate the reference frame by 2x2.

10 14. The method of claim 9 wherein said step of searching using a first filter to do a first interpolation further comprises using a bilinear filter to interpolate the reference frame by 2x2 and said step of searching using a second filter to do a second interpolation further comprises using a cubic filter to do a fine interpolation.

15 15. The method of claim 14 wherein said step of searching using a third filter to do a third interpolation further comprises using a cubic filter to do a fine interpolation.

20 16. An adaptive motion accuracy search method for estimating motion vectors in motion-compensated video coding by finding a best motion vector for a macroblock, said method comprising the steps of:

- 25
- (a) searching at a first motion accuracy for a first best motion vector of said macroblock;
 - (b) encoding said first best motion vector and said first motion accuracy;
 - (c) searching for at least one second best motion vector of said macroblock at an at least one second motion accuracy;
 - (d) encoding said at least one second best motion vector and said at least one second motion accuracy; and
 - (e) selecting the best motion vector of said first and at least one best motion vectors using rate-distortion criteria.

17. The method of claim 16 wherein said step of selecting the best motion vector using rate-distortion criteria further comprises the step of said rate-distortion criteria adapting according to the different motion accuracies to determine both the best motion vectors and the best motion accuracies.

18. The method of claim 16, said step of searching for at least one second best motion vector at an at least one second motion accuracy further comprising the step of searching for at least one second best motion vector of said macroblock at an at least one second motion accuracy that is finer than said first motion accuracy.

19. The method of claim 16 wherein said step of selecting the best motion vector using rate-distortion criteria further comprises the step of using rate-distortion criteria of the type "distortion + L*Bits" to select the best motion vector.

20. An adaptive motion accuracy search method for estimating motion vectors in motion-compensated video coding by finding a best motion vector for a macroblock, said method comprising the steps of:

- (a) searching at a motion accuracy for a best motion vector of said macroblock;
- (b) encoding said motion accuracy using a code from a VLC table that is interpreted differently at different coding units according to the associated motion vector accuracy; and
- (c) encoding said best motion vector in the respective accuracy space.

21. A system for estimating motion vectors in motion-compensated video coding by finding a best motion vector for a macroblock, said system comprising:

5

- (a) a first encoder for searching a first set of motion vector candidates in a grid of sub-pixel resolution of a predetermined square radius centered on V_1 to find a best motion vector V_2 ;
- (b) a second encoder for searching a second set of motion vector candidates in a grid of sub-pixel resolution of a predetermined square radius centered on V_2 to find a best motion vector V_3 ; and
- (c) a third encoder for searching a third set of motion vector candidates in a grid of sub-pixel resolution of a predetermined square radius centered on V_3 to find said best motion vector of said macroblock.

10

22. The system of claim 21 wherein said first, second, and third encoders are a single encoder.

METHODS FOR MOTION ESTIMATION WITH ADAPTIVE MOTION ACCURACY

ABSTRACT OF THE DISCLOSURE

5

Methods for motion estimation with adaptive motion accuracy of the present invention include several techniques for computing motion vectors of high pixel accuracy with a minor increase in computation. One technique uses fast-search strategies in sub-pixel space that smartly searches for the best motion vectors. An alternate
10 technique estimates high-accurate motion vectors using different interpolation filters at different stages in order to reduce computational complexity. Yet another technique uses rate-distortion criteria that adapts according to the different motion accuracies to determine both the best motion vectors and the best motion accuracies. Still another technique uses a VLC table that is interpreted differently at different coding units,
15 according to the associated motion vector accuracy.




FIGURE 1

FIGURE 2





FIGURE 4






FIGURE 3




FIGURE 5

FIGURE 6





FIGURE 7






FIGURE 8




FIGURE 9




FIGURE 10




FIGURE 11




FIGURE 12




FIGURE 13




FIGURE 14




FIGURE 15




FIGURE 16




FIGURE 17




FIGURE 18

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)

Approved for use through 9/30/00. OMB 0651-0032

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63)	Attorney Docket Number	KDO:190230-4
	First Named Inventor	Jordi Ribas-Corbera
	COMPLETE IF KNOWN	
	Application Number	/
	Filing Date	Concurrently herewith
	Group Art Unit	
<input checked="" type="checkbox"/> Declaration Submitted with Initial Filing	OR	<input type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)
Examiner Name		

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

METHODS FOR MOTION ESTIMATION WITH ADAPTIVE MOTION ACCURACY

the specification of which (Title of the Invention)

☒ is attached hereto

OR

☐ was filed on (MM/DD/YYYY) as United States Application Number or PCT International

Application Number and was amended on (MM/DD/YYYY) (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)	
60/146,102	07/27/1999	<input type="checkbox"/> Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)

Approved for use through 9/30/00. OMB 0651-0032

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION — Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

☐ Customer Number

OR

☒ Registered practitioner(s) name/registration number listed below

Place Customer Number Bar Code Label here

Name	Registration Number	Name	Registration Number
Karen Dana Oster	37,621		
Erich W. Merrill, Jr.	31,982		
Bruce A. Kaser	31,531		

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to: ☐ Customer Number or Bar Code Label ☒ Correspondence address below

Name	Miller Nash LLP				
Address	3500 U.S. Bancorp Tower				
Address	111 S.W. Fifth Avenue				
City	Portland	State	OR	ZIP	97204-3699
Country	USA	Telephone	(503) 224-5858	Fax	(503) 224-0155

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor:		<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle (if any))			Family Name or Surname		
Jordi			Ribas-Corbera		
Inventor's Signature					Date
Residence: City	Redmond	State	WA	Country	USA
Post Office Address	6125 145th Court NE				
Post Office Address					
City	Redmond	State	WA	ZIP	98052
Country	USA				

☒ Additional inventors are being named on the 1 supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto

Please type a plus sign (+) inside this box → ☐

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

PTO/SB/02A (3-97)
Approved for use through 9/30/98. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE



DECLARATION

ADDITIONAL INVENTOR(S) Supplemental Sheet

Page 1 of 1

Name of Additional Joint Inventor, if any:

☐ A petition has been filed for this unsigned inventor

Given Name (first and middle [if any])

Family Name or Surname

Jiandong

Shen

Inventor's
Signature

Date

Residence: City

San Jose

State

CA

Country

USA

Citizenship

China

Post Office Address

170 West Tasman

Post Office Address

City

San Jose

State

CA

ZIP

95134

Country

USA

Name of Additional Joint Inventor, if any:

☐ A petition has been filed for this unsigned inventor

Given Name (first and middle [if any])

Family Name or Surname

Inventor's
Signature

Date

Residence: City

State

Country

Citizenship

Post Office Address

Post Office Address

City

State

ZIP

Country

Name of Additional Joint Inventor, if any:

☐ A petition has been filed for this unsigned inventor

Given Name (first and middle [if any])

Family Name or Surname

Inventor's
Signature

Date

Residence: City

State

Country

Citizenship

Post Office Address

Post Office Address

City

State

ZIP

Country

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

